



ZefaTech®

PRODUCT DATA

ZEFATECH® AS 152 N

Paintable Mold Release (Non Silicone)

DESCRIPTION AND USE

ZEFATECH® AS 152 N Paintable Mold Release agent developed by our unique design. This product has best release, ideal for delicate and precise mold. No residues are remained. Using this product, defect occurrence ratio is reduced. Also, quality improvement, work hour reduction and cost saving are obtained. Additionally, it is used widely for polishing surface protection and lubrication.

ZEFATECH® AS 152 N generally uses for epoxy resin, phenol resin, rubbers, engineering plastics, ABS resin, and PVC resin.

METHOD OF USE

Clean foreign substances, carbon and injection molding residues with ZEFATECH® AS 743 anti static mold cleaner. Spray it evenly with 20-30 cm away from mold.

TECHNICAL DATA

Viscosity at 25°C : 0.80 cps
Specific Gravity : 0.70
Solidity (105°C/3hrs) : 1.0 %

CAUTIONS

Keep it in the well-ventilated place below 40°C.
Provide good ventilation.

BENEFITS

Excellent lubrication and release
Quick drying product with excellent release
No residues remained on mold
Formation of even film
Non corrosive to mold

PACKAGING

: 450 ml Aerosol Can, 12 Cans per Carton Box