



ZefaTech®

PRODUCT DATA

ZEFATECH® AS 772
Copper Gasket Adhesive

DESCRIPTION

ZEFATECH®AS 772 is an advanced characteristic of ZEFATECH® products provide non slip and non shift properties. Thereby producing a highly tenacious bond and longer lasting gasket life,as well as ease of application. The copolymer resins in ZEFATECH®AS 772 provide super strong tack and fast in 90 seconds.

ZEFATECH®AS 772 is fortified with micro fine copper particles that permeate surface irregularities and improve sealing qualities,these microfine copper particles line the heat conductive surfaces,fills surface pores,and forms a protective copper coating.

ZEFATECH®AS 772 is ideally used on all commonly used gasket materials,including asbestos,rubber,plastics,metal,etc and also use in automotive and industrial plant for equipment,installations,including pumps,pipe work,cylinder heat gaskets,and general flange gaskets. ZEFATECH®AS 772 protects gaskets against the harmful effects of extreme temperatures up to 600 degree C and high pressure.

PROPERTIES

Appearance & Odor	:Copper colour,viscous liquid with acetone odor
Solubility in Water	: Insoluble
Specific Gravity	: N/A
Melting Point	: N/A
Vapour Density (Air=1)	: > 1
Evaporation Rate (Ether = 1)	: > 1

PACKAGING : 400 ml Aerosol Can, 12 Cans per Carton Box