



# ZefaTech®

---

## PRODUCT DATA

**ZEFATECH® AS 152**  
Mold Release

**DESCRIPTION  
AND USE**

ZEFATECH® AS 152 is a non paintable mold release agent developed by our unique design.

This product has best release, ideal for delicate and precise mold. No residues are remained. Using this product, defect occurrence ratio is reduced. Also, quality improvement work hour reduction and cost saving are obtained. Additionally, it is used widely for polishing surface protection and lubrication.

ZEFATECH® AS 152 generally uses for epoxy resin, phenol resin, rubbers, engineering plastics, ABS resin, and PVC resin.

**METHOD OF  
USE**

Clean foreign substances, carbon and injection molding residues with ZEFATECH® AS 743 anti static mold cleaner. Spray it evenly with 20-30 cm away from mold.

**TECHNICAL  
DATA**

Viscosity at 25°C : 12.0 cSt  
Specific Gravity : 0.70  
Solidity (105°C/3hrs) : 2.0 %

**CAUTIONS**

Keep it in the well-ventilated place below 40°C.  
Provide good ventilation.

**BENEFITS**

Excellent lubrication and release  
Quick drying product with excellent release  
No residues remained on mold  
Formation of even film  
Non corrosive to mold

**PACKAGING**

: 450 ml Aerosol Can, 12 Cans per Carton Box